

Kawasaki

**KLX**



**EASY,  
LIGHTWEIGHT,  
& RELIABLE**

# KLX

## SPECIFICATION

Power Engine	: 4-stroke, 1-cylinder, SOHC, Air-cooled
Displacement	: 144cc
Bore x Stroke	: 58.0 x 54.4mm
Compression ratio	: 9.5:1
Fuel System Keihin	: PB20
Ignition Digital	: DC-CDI
Transmission	: 5-speed with wet multi-disc manual clutch
Final Drive Chain	
Performance Front Suspension / Wheel Travel	: 33mm telescopic fork / 7.1 in
Rear Suspension / Wheel Travel Uni-Trak®	: linkage system and single shock with 5-way preload adjustability / 7.1 in
Front Tire	: Size 70/100-17
Rear Tire	: Size 90/100-14
Front Brakes Single	: 220mm petal disc with a dual-piston caliper
Rear Brakes Single	: 186mm petal disc with single-piston caliper
Frame Type	: High-Tensile steel, box-section perimeter
Rake/Trail	: 27° / 3.3 in
Overall Length	: 71.7 in
Overall Width	: 31.1 in
Overall Height	: 41.3 in
Ground Clearance	: 9.3 in
Seat Height	: 30.7 in ( 779,78 mm )
Curb Weight	: 205.0 lb/ berat basah 92,9864 KG
Fuel Capacity	: 1.5 gal/ 5,67 liter
Wheelbase	: 49.6 in
Warranty 6 Months	

### WARNING

- This vehicle is an off-road vehicle only and was not manufactured for use on public streets, roads or highway.
- Use your bike legally.

